Ce récepteur satellite de couleur argentée qui porte le nom de NanoXX 9400 a des dimensions très compactes. Pas trop grand, mais assez grand pour par contre pour offrir de la place sur le panneau arrière à toutes les connexions les plus importantes – y compris deux connecteurs péritel (scart). Sur le devant, ce récepteur possède les touches de com mande standard, plus deux logements PCMCIA ainsi que deux lecteurs de cartes à puce (avec licence pour les systèmes de cryptage Conax et X-Crypt) qui peu vent facilement être accédés.

NanoXX 9400

Un récepteur remarquable à balayage aléatoire

NANOXX

TECHNIC DATA	
Supplier	NanoXX www.nanoxx.info
Model	NanoXX 9400
Power Supply	90 ... 250 V AC
Power Consumption	8/13 Watt (Stand-By/Off)
Size	300 x 230 x 63 mm
Weight	1620 g
DiSEqC	1.0, 1.1, 1.2 (with GotoX), USALS
Satellites	max. 100
RF-Modulator	No
Program Listings	TV, Radio, Favorites
Teletext	800 Page Memory
EPG	Four Channel Display, whole week with program details
Timer	EPG-programmable
Front View	Stand-By, 4 Digit Display, Menu, OK, 4 Arrows
Rear View	IF In, IF Out, RS-232, USB, 3xRCA (Audio L/R, Video), 2xSCART, Main Switch, Power Supply Jack
Upgrades	Via USB Stick

\\ONEMEDIA\D\nano/nanoxx_9400.ai

intersonic

APPLICATIONS ELECTRONIQUES & INFORMATIQUES

Intersonic
Pascal BAUD
avril 2008
NANO XX 9400
022 797 4444